Product introduction

Product name] disposable mask (no exhalation valve)
Product Grade] Civil Protection
Number of products] 25PCS / box
Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton +
on-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
Product performance] The appearance of the mask is neat and intact, and the surface must not
e damaged or stained.
he periphery of the mask is flat and densely pressed, and there must be no shedding.
he breaking tension at the connection point between the earband of the mask and the body
nust not be less than 10N, and the welding points of the earband are evenly distributed at the
our corners of the mask body.
he elasticity of the earband is moderate, and there are no breaks or snags on the surface. The
ose bridge clamp is made of a plastic material and is located in the middle of the mask body.
can be subjected to free plasticity under external force, and its shape does not change after
e-stressing. The filtering effect of the mask should not be less than 95%.
Scope of use] Suitable for protection in the process of processing coal, iron ore and
uartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
nstructions]
. Hold the mask in your hand, with your fingertips in the nose clip position, and let the
arbands hang freely.
. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can
e close to the nose, and the ear band is pulled to the position behind the ear.
. Use both hands to adjust the shape of the nose strip to ensure tightness.
. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the
ose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.
Executive Standard] GB 2626-2006
Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
Production date] see certificate of conformity
Valid Date] This product is valid for two years
Storage conditions] 1. This product should be stored in a room with relative humidity not
xceeding 80%, no corrosive gas or good ventilation.
. The product must not be squeezed too much during transportation to avoid damage to the
ackaging.
Contraindications] Use with caution to those who are allergic to propane nonwovens.
Precautions]
.Failure to use or exceed the limits of use of this product, or to wear it during contact with
armful substances will reduce the protective function of this product.
.Before using this product, the wearer must know the correct method of wearing a mask that
neets safety and hygiene standards.
.Discard the mask or replace it with a new one (excessive blockage causes the wearer to
reathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the
ontaminated site.
Manufacturer: Chun Lam Group(International) Limited.
el: +86-769-86248333 Fax:+86 -769-86248982
egistered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu,
hang'an Town, Dongguan City
roduction address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu,
hang'an Town, Dongguan City

Product introduction

Product name] disposable mask (no exhalation valve)
Product Grade] Civil Protection
Number of products] 25PCS / box
Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton +
on-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
Product performance] The appearance of the mask is neat and intact, and the surface must not
e damaged or stained.
he periphery of the mask is flat and densely pressed, and there must be no shedding.
he breaking tension at the connection point between the earband of the mask and the body
nust not be less than 10N, and the welding points of the earband are evenly distributed at the
our corners of the mask body.
he elasticity of the earband is moderate, and there are no breaks or snags on the surface. The
ose bridge clamp is made of a plastic material and is located in the middle of the mask body.
can be subjected to free plasticity under external force, and its shape does not change after
e-stressing. The filtering effect of the mask should not be less than 95%.
Scope of use] Suitable for protection in the process of processing coal, iron ore and
uartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
nstructions]
. Hold the mask in your hand, with your fingertips in the nose clip position, and let the
arbands hang freely.
. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can
e close to the nose, and the ear band is pulled to the position behind the ear.
. Use both hands to adjust the shape of the nose strip to ensure tightness.
. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the
ose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.
Executive Standard] GB 2626-2006
Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
Production date] see certificate of conformity
Valid Date] This product is valid for two years
Storage conditions] 1. This product should be stored in a room with relative humidity not
xceeding 80%, no corrosive gas or good ventilation.
. The product must not be squeezed too much during transportation to avoid damage to the
ackaging.
Contraindications] Use with caution to those who are allergic to propane nonwovens.
Precautions]
.Failure to use or exceed the limits of use of this product, or to wear it during contact with
armful substances will reduce the protective function of this product.
.Before using this product, the wearer must know the correct method of wearing a mask that
neets safety and hygiene standards.
.Discard the mask or replace it with a new one (excessive blockage causes the wearer to
reathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the
ontaminated site.
Manufacturer: Chun Lam Group(International) Limited.
el: +86-769-86248333 Fax:+86 -769-86248982
egistered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu,
hang'an Town, Dongguan City
roduction address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu,
hang'an Town, Dongguan City

Product introduction

[Product name] disposable mask (no exhalation valve)
[Product Grade] Civil Protection
[Number of products] 25PCS / box
[Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
[Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton + non-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
[Product performance] The appearance of the mask is neat and intact, and the surface must not be damaged or stained.
The periphery of the mask is flat and densely pressed, and there must be no shedding.
The breaking tension at the connection point between the earband of the mask and the body must not be less than 10N, and the welding points of the earband are evenly distributed at the four corners of the mask body.
The elasticity of the earband is moderate, and there are no breaks or snags on the surface. The nose bridge clamp is made of a plastic material and is located in the middle of the mask body.
It can be subjected to free plasticity under external force, and its shape does not change after de-stressing. The filtering effect of the mask should not be less than 95%.
[Scope of use] Suitable for protection in the process of processing coal, iron ore and quartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
[Instructions]
1. Hold the mask in your hand, with your fingertips in the nose clip position, and let the earbands hang freely.
2. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can be close to the nose, and the ear band is pulled to the position behind the ear.
3. Use both hands to adjust the shape of the nose strip to ensure tightness.
4. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the nose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.

[Executive Standard] GB 2626-2006
[Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
[Production date] see certificate of conformity
[Valid Date] This product is valid for two years
[Storage conditions] 1. This product should be stored in a room with relative humidity not exceeding 80%, no corrosive gas or good ventilation.
2. The product must not be squeezed too much during transportation to avoid damage to the packaging.
[Contraindications] Use with caution to those who are allergic to propane nonwovens.
[Precautions]
1.Failure to use or exceed the limits of use of this product, or to wear it during contact with harmful substances will reduce the protective function of this product.
2.Before using this product, the wearer must know the correct method of wearing a mask that meets safety and hygiene standards.
3.Discard the mask or replace it with a new one (excessive blockage causes the wearer to breathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the contaminated site.

Manufacturer: Chun Lam Group(International) Limited.
Tel: +86-769-86248333 Fax:+86 -769-86248982
Registered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City
Production address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City

Product introduction

[Product name] disposable mask (no exhalation valve)
[Product Grade] Civil Protection
[Number of products] 25PCS / box
[Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
[Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton + non-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
[Product performance] The appearance of the mask is neat and intact, and the surface must not be damaged or stained.
The periphery of the mask is flat and densely pressed, and there must be no shedding.
The breaking tension at the connection point between the earband of the mask and the body must not be less than 10N, and the welding points of the earband are evenly distributed at the four corners of the mask body.
The elasticity of the earband is moderate, and there are no breaks or snags on the surface. The nose bridge clamp is made of a plastic material and is located in the middle of the mask body.
It can be subjected to free plasticity under external force, and its shape does not change after de-stressing. The filtering effect of the mask should not be less than 95%.
[Scope of use] Suitable for protection in the process of processing coal, iron ore and quartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
[Instructions]
1. Hold the mask in your hand, with your fingertips in the nose clip position, and let the earbands hang freely.
2. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can be close to the nose, and the ear band is pulled to the position behind the ear.
3. Use both hands to adjust the shape of the nose strip to ensure tightness.
4. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the nose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.

[Executive Standard] GB 2626-2006
[Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
[Production date] see certificate of conformity
[Valid Date] This product is valid for two years
[Storage conditions] 1. This product should be stored in a room with relative humidity not exceeding 80%, no corrosive gas or good ventilation.
2. The product must not be squeezed too much during transportation to avoid damage to the packaging.
[Contraindications] Use with caution to those who are allergic to propane nonwovens.
[Precautions]
1.Failure to use or exceed the limits of use of this product, or to wear it during contact with harmful substances will reduce the protective function of this product.
2.Before using this product, the wearer must know the correct method of wearing a mask that meets safety and hygiene standards.
3.Discard the mask or replace it with a new one (excessive blockage causes the wearer to breathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the contaminated site.

Manufacturer: Chun Lam Group(International) Limited.
Tel: +86-769-86248333 Fax:+86 -769-86248982
Registered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City
Production address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City

Product introduction

[Product name] disposable mask (no exhalation valve)
[Product Grade] Civil Protection
[Number of products] 25PCS / box
[Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
[Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton + non-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
[Product performance] The appearance of the mask is neat and intact, and the surface must not be damaged or stained.
The periphery of the mask is flat and densely pressed, and there must be no shedding.
The breaking tension at the connection point between the earband of the mask and the body must not be less than 10N, and the welding points of the earband are evenly distributed at the four corners of the mask body.
The elasticity of the earband is moderate, and there are no breaks or snags on the surface. The nose bridge clamp is made of a plastic material and is located in the middle of the mask body.
It can be subjected to free plasticity under external force, and its shape does not change after de-stressing. The filtering effect of the mask should not be less than 95%.
[Scope of use] Suitable for protection in the process of processing coal, iron ore and quartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
[Instructions]
1. Hold the mask in your hand, with your fingertips in the nose clip position, and let the earbands hang freely.
2. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can be close to the nose, and the ear band is pulled to the position behind the ear.
3. Use both hands to adjust the shape of the nose strip to ensure tightness.
4. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the nose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.

[Executive Standard] GB 2626-2006
[Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
[Production date] see certificate of conformity
[Valid Date] This product is valid for two years
[Storage conditions] 1. This product should be stored in a room with relative humidity not exceeding 80%, no corrosive gas or good ventilation.
2. The product must not be squeezed too much during transportation to avoid damage to the packaging.
[Contraindications] Use with caution to those who are allergic to propane nonwovens.
[Precautions]
1.Failure to use or exceed the limits of use of this product, or to wear it during contact with harmful substances will reduce the protective function of this product.
2.Before using this product, the wearer must know the correct method of wearing a mask that meets safety and hygiene standards.
3.Discard the mask or replace it with a new one (excessive blockage causes the wearer to breathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the contaminated site.

Manufacturer: Chun Lam Group(International) Limited.
Tel: +86-769-86248333 Fax:+86 -769-86248982
Registered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City
Production address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City

Product introduction

[Product name] disposable mask (no exhalation valve)
[Product Grade] Civil Protection
[Number of products] 25PCS / box
[Specifications Model] Ear-Hanging Half Mask L: 160mm * 100mm
[Product structure] It is made of non-woven fabric + melt-blown fabric + spunlace cotton + non-woven fabric, nose bridge clip, ear band, etc. It is non-sterile and provides one-time use.
[Product performance] The appearance of the mask is neat and intact, and the surface must not be damaged or stained.
The periphery of the mask is flat and densely pressed, and there must be no shedding.
The breaking tension at the connection point between the earband of the mask and the body must not be less than 10N, and the welding points of the earband are evenly distributed at the four corners of the mask body.
The elasticity of the earband is moderate, and there are no breaks or snags on the surface. The nose bridge clamp is made of a plastic material and is located in the middle of the mask body.
It can be subjected to free plasticity under external force, and its shape does not change after de-stressing. The filtering effect of the mask should not be less than 95%.
[Scope of use] Suitable for protection in the process of processing coal, iron ore and quartz-containing minerals or processing cotton, flour and various dusts and non-oily mists.
[Instructions]
1. Hold the mask in your hand, with your fingertips in the nose clip position, and let the earbands hang freely.
2. Put the mask on the face, and at the same time, make sure that the nose strip of the mask can be close to the nose, and the ear band is pulled to the position behind the ear.
3. Use both hands to adjust the shape of the nose strip to ensure tightness.
4. Wear test: Cover the mask with both hands and exhale. If you feel any gas coming out of the nose, tighten the nose clip. If air leaks from the edges, readjust to ensure tightness.

[Executive Standard] GB 2626-2006
[Function and use] Close-fitting mask for covering the user's mouth, nose and jaw
[Production date] see certificate of conformity
[Valid Date] This product is valid for two years
[Storage conditions] 1. This product should be stored in a room with relative humidity not exceeding 80%, no corrosive gas or good ventilation.
2. The product must not be squeezed too much during transportation to avoid damage to the packaging.
[Contraindications] Use with caution to those who are allergic to propane nonwovens.
[Precautions]
1.Failure to use or exceed the limits of use of this product, or to wear it during contact with harmful substances will reduce the protective function of this product.
2.Before using this product, the wearer must know the correct method of wearing a mask that meets safety and hygiene standards.
3.Discard the mask or replace it with a new one (excessive blockage causes the wearer to breathe; the mask is damaged.) If you feel dizzy, irritated or other discomfort, please leave the contaminated site.

Manufacturer: Chun Lam Group(International) Limited.
Tel: +86-769-86248333 Fax:+86 -769-86248982
Registered address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City
Production address: 8 East Street of Zhenyuan Road , the forth Industrial Area of Caiwu, Chang'an Town, Dongguan City